

ASYG12KMCF





Unit Type		Wall Mounted
Remote Controller		IR Included
Nominal Cooling Capacity	(kW)	3.4
Nominal Heating Capacity	(kW)	4.0
Height	(mm)	270
Width	(mm)	834
Depth	(mm)	222
Weight	(kg)	10
Airflow Rate - Cooling - High	(m3/h)	700
Airflow Rate - Heating - High	(m3/h)	780
Sound Pressure Level - Cooling - High	(dB(A))	40
Sound Pressure Level - Cooling - Low	(dB(A))	20
Sound Pressure Level - Heating - High	(dB(A))	42
Sound Pressure Level - Heating - Low	(dB(A))	22
Sound Power Level - Cooling - High	(dB(A))	55
Sound Power Level - Heating - High	(dB(A))	58
Moisture Removal	(l/h)	1.8
Refrigerant Type (Global Warming Potential)		R32 (675)
Liquid Pipe Size		1/4"
Gas Pipe Size		3/8"
Unit Power Supply		From Outdoor Unit

Document Downloads

<u>Airflow - Fan Curve</u> Controls & Accessories <u>Dimensional Drawing</u> **Electrical Characteristics Function Settings** Inputs & Outputs **Installation Manual** Noise Curve

Operation Manual

Product Image Spare Parts List All Pages **Specifications** Wiring Diagram

Unit: mm **Related Items**

AOYG12KMCC AOYG14KBTA2 AOYG18KBTA2 AOYG18KBTA3 AOYG24KBTA3 AOYG30KBTA4 AOYG36KBTA5 UTYRNRYZ5 <u>UTYRSNYM</u> UTYXWZXZ5 UTYTWRXZ2 **UTYTERX UTYVTGX UTYVTGXV**

3.4kW Outdoor Unit - R32 Single Phase 4.0kW 2 Way Multi Outdoor Unit - R32 1 Ph 5.0kW 2 Way Multi Outdoor Unit - R32 1 Ph 5.4kW 3 Way Multi Outdoor Unit - R32 1 Ph 6.8kW 3 Way Multi Outdoor Unit - R32 1 Ph 8.0kW 4 Way Multi Outdoor Unit - R32 1 Ph 10.0kW 5 Way Multi Outdoor Unit - R32 1 Ph LCD Wired Remote Controller

Simplified Wired Remote Controller External Connect Kit

Communication Kit External switch controller

Splits Network Converter (DC Powered) Splits Network Converter (AC Powered)

	270
	Outline of indoor unit 327
9.5	273 273 54
220	CZZ
43	63 182 182 63
-,	48 346 356 84 for pipe inlet Ø65

[•]Specifications and design are subject to change without notice for further improvement.

[·] Actual products' colors may be different from the colors shown in this printed material.